

## Z40 MINI-SPLIT CONDENSATE PUMP

### Submittal Information

Part No.	18102
Document No.	SPEC18102
Date	2025-02-05
Revision	01

### General Properties

- Power supply: 100-240V AC 50/60Hz <4W
- Max.flow: 40L(10.57 gal)/H, range from 20-40L(5.28-10.57 gal)/H
- Max.recommended head: 20m (65.62 ft)
- Max.suction lift: 2m (6.56 ft)
- Max.unit output: 46KW / 157,000 Btu/h
- Max.water temperature: 40°C (104°F)
- Discharge tube: 6mm (1/4 in) ID
- Class: II appliance
- Protection: Fully potted, IP-45

### Specification

Item No.	Description	Std. Pkg	U/M
18102	Z40 Mini-split Pump, Upgrade Sensor, Dual Vol, 10.6 GPH	1	EA

### Features

- Operates with low noise for a quiet environment.
- Features safe and reliable water detection using a capacitive sensor.
- Offers large flow capacity for efficient condensate drainage.
- Automatic flow adjustment reduces noise and extends pump lifespan.
- Designed for easy cleaning and maintenance.



### Accessories List

- Assembled
- Assembled inline reservoir, including:
  - lid & capacitor plate
  - fn key (Fn)
  - status indicator
  - filter
  - reservoir
  - breather hole 6mm (1/4 in) OD
- Plug connector
- 5 ft length of 1/4 in ID vinyl tube
- 6 in Silicone tube
- Power cable
- 1A fuse
- Anti-siphon valve
- Check valve
- 3M tape 2 x 2 in x 3/4 in x 1/32 in
- 3M tape 1 x 2 in x 3/4 in x 3/32 in
- Nylon clamps 4 x 8 in x 5/32 in

### Performance Data

