

BRAIDED VINYL TUBING

Submittal Information

Part No. 12407-12411
 Document No. SPEC12407
 Date 2025-02-14
 Revision 02

General Properties

- Material: PVC & Polyester Reinforces Braiding
- Service Temperature Range: 23 -140 F(±5%)
- Color: Clear

Specification

Item No.	I.D. (inch)	O.D. (inch)	Wall Thickness (inch)	W.P. PSI	B.P. PSI	Hardness	Length (feet)	U/M	Std. Pkg.
12407	0.250	0.447	0.098	200	800	90	50 (±3%)	RL	1
12408	0.375	0.572	0.098	200	800	90	50 (±3%)	RL	1
12409	0.500	0.697	0.098	150	600	90	50 (±3%)	RL	1
12410	0.625	0.822	0.098	150	600	90	50 (±3%)	RL	1
12411	0.750	0.986	0.118	150	600	90	50 (±3%)	RL	1

Features

- Braided PVC construction.
- Smooth, dense bore maximizes flow and reduces sediment buildup.
- Light weight and flexible, can be cut to size as needed.
- Resistant to acids, alkalis, a variety of chemicals, gases, and liquids.
- Has four times the working pressure of single wall PVC.

Applications

- Use for refrigeration and air conditioning condensation drains.
- Use for aquariums, drain hoses, bath and spa jets, dishwasher inlets and more.
- Cannot be used as tubing for drinking water.

