

CLEAR VINYL TUBING

Submittal Information

Part No. 12401-12406
Document No. SPEC12401
Date 2024-02-14
Revision 02

General Properties

- Material: PVC
- Service Temperature Range: 23 -140 F(±5%)
- Color: Clear

Specification

Item No.	I.D. (inch)	O.D. (inch)	Wall Thickness (inch)	W.P. PSI	B.P. PSI	Hardness	Length (feet)	U/M	Std. Pkg.
12401	0.250	0.329	0.039	75	300	90	100(±3%)	RL	1
12402	0.375	0.474	0.049	75	300	90	100 (±3%)	RL	1
12403	0.500	0.598	0.049	45	180	90	100 (±3%)	RL	1
12404	0.625	0.728	0.051	45	180	90	100 (±3%)	RL	1
12405	0.750	0.868	0.059	45	180	90	100 (±3%)	RL	1
12406	0.875	0.993	0.059	45	180	90	50 (±3%)	RL	1

Features

- Super smooth dense bore maximizes flow and reduces sediment build up.
- Easy to shape, bend and install, can be cut to size as needed.
- Can be used in a wide variety of settings involving chemicals, gases, and liquids.
- Resistant to acids, alkalis, a variety of chemicals, gases, and liquids.
- Great for low-pressure applications because of the high-quality material.

Applications

- Use for refrigeration and air conditioning condensation drains.
- Use for aquariums, drain hoses, bath and spa jets, dishwasher inlets and more.
- Cannot be used as tubing for drinking water.

